



Tema, Abattoir Area, Ghana, +233246672676, t.kostyk@yuko.com.gh


YUKO MODELUX EP2

Print



MULTIPURPOSE LITHIUM GREASE.

ENABLED PACKING

 Tin bucket 17,0kg  Barrel 170kg

Description

YUKO MODELUX EP2, lithium hydroxystearate thickened, provides an exceptionally high wear and rust protection, water resistance.

Recommended for use in major types of industrial equipment, including equipment operating in severe conditions at high unit pressures or shock loads, including the equipment, where the presence of moisture is typical, as a universal lubrication of anti-friction bearings and sliding bearings, bushings, fingers friction and other nodes in normal operating conditions

BENEFITS

- Reduced wear under heavy or shock loading and vibration;
- Provides excellent protection against rust and corrosion;
- Resistant to water washout;
- Provides a high reliability and safety of equipment;
- Increases bearing life in humid environments

Temperature range



Compliance

NLGI 2

DIN 51502: KP2K-30

Typical characteristics

thickening agent	Lithium hydroxystearate
Dropping point, ° C	200
Penetration, mm • 10 -1	275
Efficient viscosity at -20 ° C, Pa • s, no more	343
Colloid stability, %, no more	13
Tribological Characteristics on a 4-ball machine, N, not less than	
- Welding load (Pc)	2450
- Critical load (Pk)	820
- Index Badass (From)	350

PRODUCT DESCRIPTION. Technical Data Sheet (TDS).

YUKO MODELUX EP2

<http://yuko.com.gh/greases/39-yuko-modelux-ep2.html>

[Come back](#)