



Tema, Abattoir Area, Ghana, +233246672676, t.kostyk@yuko.com.gh

# YUKO MOTOMIX 2T

Print



## MINERAL MOTOR OIL FOR TWO STROKE ENGINES.

### ENABLED PACKING

- Canister 1L

### Description

Intended for lubricating systems of air-cooled two stroke engines of modern motorcycles, motorbikes, chainsaws and other machinery.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

### BENEFITS

- Provides good lubricating, anti-wear, anticorrosion and detergent properties due to the active additives package;
- Provide carbon removal from the combustion chamber;
- The possibility of year-round use;
- Provides long service life of ignition plug;
- Minimizes maintenance costs;

### Temperature range



### Compliance

API TC

JASO FB

### Typical characteristics

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	8.5
Density at 20°C, kg/m <sup>3</sup>	890
Viscosity index	98
Alkalinity, mg KOH/g	0.85
Flash point in open crucible, °C	215
Pour point, °C	-26

**PRODUCT DESCRIPTION. Technical Data Sheet (TDS).**

**YUKO MOTOMIX 2T**

<http://yuko.com.gh/oils/motor-oils/2t/58-uko-motomix-2t.html>

[Come back](#)