



Tema, Abattoir Area, Ghana, +233246672676, t.kostyk@yuko.com.gh

YUKO SYNTHETIC 5W-30

Print



SYNTHETIC HIGH-TECH MOTOR OIL.

ENABLED PACKING

Canister 4L Barrel 200L

Description

Intended for modern gasoline and diesel engines of passenger cars and vans from Japan and US carmakers.

Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

Provides improved safety as compared to mineral and semi-synthetic oils.

Special low-ash formula. Has an extended drain interval. Compatible with injector and multivalve engines, including turbocharged ones, with intercooler and catalyst.

Compliance

SAE 5W-30
API SM/CF
ACEA A3/B3/B4
VW 502.0/505.00
MB 229.3
BMW LL-01
Opel GM-LL-025

Typical characteristics

Kinematic viscosity at 100°C, mm ² /s	11.9
Density at 20°C, kg/m ³	860
Viscosity index	150
Alkalinity, mg KOH/g	9.75
Flash point in open crucible, °C	210
Pour point, °C	-33

Benefits

- Provides a reliable engine protection under various conditions incl. extreme operating mode;
- Optimum for the use both in urban cycle and cross-country conditions;
- Due to its fluidity reduces fuel consumption;
- Significantly extends engine service life due to multipurpose additives package, with excellent low temperature, antifriction, anticorrosion, detergent and antioxidant properties;
- Maintains effectiveness for maximum long period, which allows to extend significantly oil drain intervals;
- Due to superior viscosity/temperature properties, provides safe engine start at low temperatures in winter, including the regions with harsh weather conditions in winter;
- Conforms to modern requirements of world leaders in equipment manufacture concerning oil consumption, volatility, energy saving.

Temperature range



PRODUCT DESCRIPTION. Technical Data Sheet (TDS).

YUKO SYNTHETIC 5W-30

<http://yuko.com.gh/oils/motor-oils/for-passenger-transport/4-yuko-synthetic-5w-30.html>

[Come back](#)