



Tema, Abattoir Area, Ghana, +233246672676, t.kostyk@yuko.com.gh


# YUKO HIGHGEAR MAX (SAE 140, GL-4)

Print



## HIGH QUALITY TRANSMISSION GEAR OIL.

### ENABLED PACKING

 Barrel 200L

### Description

High quality transmission gear oil for driving gears (incl. hypoid) and differentials of all types of transmissions for passenger cars and commercial vehicles. Peculiar by outstanding shear stability and meets the requirements of GL-4 standard. Suitable for effective use in hypoid gears working under maximum loads. Excellent lubricating properties ensure soft shifting of conic thimbles and self-locking differentials.

### Compliance

SAE 140

API GL-4

### Typical characteristics

Kinematic viscosity at 100°C, mm<sup>2</sup>/s 22.1

Flash point, °C 260

Density at 20°C, kg/m<sup>3</sup> 900

### BENEFITS

- It provides soft shifting and noiseless transmission work;
- Good protection for engine parts against corrosion and deposits;
- Extends the service life of gearbox parts.
- Good oxidation and thermal oxidative stabilities;

### Temperature range



**PRODUCT DESCRIPTION. Technical Data Sheet (TDS).**

**YUKO HIGHGEAR MAX (SAE 140, GL-4)**

<http://yuko.com.gh/oils/transmission/transmission-for-commercial-transport/56-yuko-highgear-max-sae-140-gl-4.html>

[Come back](#)