

## De-Fence Swing Gates



### Product Features:

- Self-closing single swing gates.
- Kit includes all brackets and panels.
- Welded tubular frame with mesh in-fill.
- Gates available in single or double height models.
- Gate can swing left or right.
- Full installation service available.
- Designed to comply with AS 4024.1-2019

## Swing Gates designed to complement the De-Fence machinery guarding safety fence

Swing Gates are unique to the De-Fence machinery guarding system and can be installed as an addition to safety guarding around machinery or working areas throughout the plant by creating access to equipment or pedestrian walkways.





Available in single or double height models, each kit contains all brackets allowing left or right hand operation, and panels that include a welded tubular frame and mesh in-fill panel.

Our unique bushing system for all connections prevents rattling and noise while allowing panels to swing through 180 degrees. This feature also enables panels to come off the posts at any angle.






### Made to your requirements

Our De-Fence swing gates are custom made to suit your specifications. If you are interested, please contact our sales team for a quote.






Code	Image	Product Name
DFADSWG1500S		De-Fence Double Height Swing Gate - 1425mm Opening
DFADSWG1000S		De-Fence Double Height Swing Gate - 925mm Opening
DFASSWG1500S		De-Fence Single Height Swing Gate - 1425mm Opening
DFASSWG1000S		De-Fence Single Height Swing Gate - 925mm Opening

## Accessories

Code	Image	Product Name
DF-GKP		De-Fence Gate Kick Plate 300 x 200 x 3mm
DFA-GS		De-Fence Gate Stop Kit - Zinc Plated
DF-LL		De-Fence General Purpose Gate Latch
DF-LLR		De-Fence Remote Gate Latch Release
DF-LB		De-Fence Security Lock-bolt

Description:	Push open/adjustable spring closure.
Gate Swing:	90 degrees.
Maximum Opening:	1425mm wide.
Minimum Opening:	925mm wide.
Mounting Type:	Surface mounted posts.
Gate Type:	Tubular steel frame with 3 x 25mm mesh.
Gate Height:	1260 or 2410mm.
Finish:	Powder coated.

-  [Should pedestrian safety gates swing inwards or outwards?](#)
-  [Is there an Australian Standard that specifies how machinery guarding should be constructed and installed?](#)

 We are currently compiling a list of additional services that might apply to this product.

**Related Products:**



[De-Fence Steel Posts](#)

[De-Fence Polycarbonate Panels](#)

[De-Fence Sliding Gates](#)

[De-Fence Bracket Kits](#)

[De-Fence Mesh Panels](#)