

Retractable Bollards



Medium security parking and access control bollard

Retractable bollards are designed for medium security applications such as traffic and parking control. They offer a simple, trouble free operation proven over many years of installation.

The retractable bollard is now available with a choice of two different materials. The BR900 has a 5mm thick mild steel bollard that is galvanised before being powder coated in hi-vis safety yellow with two reflective bands. The BR900-SS has a 3.05mm thick 316 marine grade stainless steel bollard. As this model is designed for more architectural applications it does not include reflective bands.

Locking Procedure

Step 1 Insert key so that handle is facing out on 'short' side of the cap

Step 2 With the key inserted, rotate in counterclockwise direction. The bollard should now be unlocked

Step 3 Lift bollard until fully extended.



Note: A retractable bollard should not be used where high security locking is required, such as car yards etc. For these applications insurance companies insist on our <u>Cam-lok Removable Bollards</u>.



Product Features:



- Round 90mm diameter bollard locks in both extended and retracted positions.
- Mild steel hot dip galvanised with a powder coated finish or 316 marine grade stainless steel.
- Galvanised in-ground casing.
- Black anti-slip top surface and two reflective bands on powder coated model.
- Two unique, low cost 'T' handle keys supplied per order with additional keys available for purchase.
- Trouble free design with only two moving parts.
- Internal locking system can't be tampered with or fouled by dirt or water.

Code	Image	Product Name
BRKEY-P	9	"T" Handle Key for Retractable/Tee-lok Bollard
BR900-SS	Ļ	Retractable Bollard 900mm - 316 Stainless Steel
BR900-G		Retractable Bollard 900mm - Galvanised
BR900	ļ	Retractable Bollard 900mm - Galvanised and Powder Coated
BR900R-SS		Retractable Bollard Replacement 900mm - 316 Stainless Steel
BR900R-G		Retractable Bollard Replacement 900mm - Galvanised
BR900R		Retractable Bollard Replacement 900mm - Galvanised and Powder Coated

Part No.	Bollard Diameter	Height above ground	Depth below ground	Wall thickness	In-ground casing diameter	Shipping weight (kgs)	Operating weight (kgs)	Finish
BR900*	90	900	1150	5	140	41.5	12.5	HDG+PC
BR900-G	90	900	1150	5	140	41.5	12.5	HDG
BR900-SS*	90	900	1150	3.05	140	38	8.8	SS


Note: All dimensions in mm. Finish: Hot Dip Galvanised (HDG), Powder Coated (PC), or 316 Stainless Steel (SS). *Each order of one or more bollards is supplied with 2x T-handle keys.

• We are currently compiling a list of additional services that might apply to this product.

Related Products:







Removable Bollards Inground Cam-Lok <u>Removable Bollards In-</u> ground Sleeve-Lok