

1300 55 33 20

Galvanised U-Bars Double Rail Steel



One-piece double rail u-bars

A modular one-piece design U-bar barrier with fully welded knee rail. Suitable for pedestrian barriers at crossing points or traffic management in and around factory/warehouse areas.

Manufactured from 3mm wall steel pipe 48mm in diameter and hot dip galvanised as standard. Available in either surface mount or below ground models. All models stand 1051mm high above ground with a fully welded knee rail at 570mm high.

Ideal for schools, shopping centres, walkways or warehouses. The fully welded and galvanised one-piece construction makes installation a quick and simple operation. No assembly required.

Part Numbers

Product Features:



- Three sizes available in below ground or surface mount models.
- Heavy 3mm wall, 48.3mm diameter pipe.
- Fully welded one-piece construction.
- All models are galvanised and powder coated or galvanised only.
- Supplied ready for installation with no assembly required.

Code	Image	Product Name	
UBD150BG-G		U-Bar Double Rail 1.5m Below Ground - Galvanised	
UBD150BG	P	U-Bar Double Rail 1.5m Below Ground - Galvanised and Powder Coated	

Code	Image	Product Name
UBD150SM-G		U-Bar Double Rail 1.5m Surface Mounted - Galvanised
UBD150SM	\square	U-Bar Double Rail 1.5m Surface Mounted - Galvanised and Powder Coated
UBD100BG-G	A	U-Bar Double Rail 1m Below Ground - Galvanised
UBD100BG	A	U-Bar Double Rail 1m Below Ground - Galvanised and Powder Coated
UBD100SM-G		U-Bar Double Rail 1m Surface Mounted - Galvanised
UBD100SM	A	U-Bar Double Rail 1m Surface Mounted - Galvanised and Powder Coated
UBD200BG-G		U-Bar Double Rail 2m Below Ground - Galvanised
UBD200BG	\square	U-Bar Double Rail 2m Below Ground - Galvanised and Powder Coated
UBD200SM-G		U-Bar Double Rail 2m Surface Mounted - Galvanised
UBD200SM	\square	U-Bar Double Rail 2m Surface Mounted - Galvanised and Powder Coated

Part No.	Post Diameter	Overall Width	Height above ground	Depth below ground	Wall thickness	Base plate L x W	Base plate thickness	Kgs	Finish
UBD100SM	48.3	1000	1040	_	3	150 x 75	10	16	HDG+PC
UBD100BG	48.3	1000	1051	280	3	-	_	16	HDG+PC
UBD100SM-G	48.3	1000	1040	_	3	150 x 75	10	16	HDG
UBD100BG-G	48.3	1000	1040	300	3	-	_	16	HDG
UBD150SM	48.3	1500	1040	_	3	150 x 75	10	19.5	HDG+PC
UBD150BG	48.3	1500	1040	300	3	_	_	19.5	HDG+PC
UBD150SM-G	48.3	1500	1040	_	3	150 x 75	10	19.5	HDG

Part No.	Post Diameter	Overall Width	Height above ground	Depth below ground	Wall thickness	Base plate L x W	Base plate thickness	Kgs	Finish
UBD150BG-G	48.3	1500	1040	300	3	_	_	19.5	HDG
UBD200SM	48.3	2000	1040	-	3	150 x 75	10	23.5	HDG+PC
UBD200BG	48.3	2000	1040	300	3	_	_	23.5	HDG+PC
UBD200SM-G	48.3	2000	1040	_	3	150 x 75	10	23.5	HDG
UBD200BG-G	48.3	2000	1040	300	3	_	_	23.5	HDG

Cotton On

() We are currently compiling a list of additional services that might apply to this product.

Related Products:



Galvanised Hoop Bollards Heavy Duty Steel

Mezzanine Roll-Over Gate

Mezzanine Double-Boom Gate

Galvanised U-Bars Heavy Duty Steel

Removable Safety Rail System